

FABLEC

ABS - Economy Range of General Purpose Plastic Enclosures



MATERIAL	ABS Plastic			
OPERATING TEMPERATURE	-30° C to + 90° C			
GLOW WIRE CAPABILITY / FLAMMABILITY	960° / UL94 V0			
EXPECTED UV LIFE (DIRECT EXPOSURE)	2-3 Years (6 Years - Indirect exposure)			
IP LEVEL	IP55			
SECURITY LEVEL	1	2	3	4
ENVIRONMENT (INDOOR/OUTDOOR)	Indoor and Outdoor use			



Part Number	Description	H	W	D	QTY
FEP-0014	ABS Enclosure - Standard Grey Lid	100	100	70	80
FEP-0016	ABS Enclosure - Standard Grey Lid	100	100	90	60
FEP-0015	ABS Enclosure - Standard Transparent Lid	100	100	70	80
FEP-0017	ABS Enclosure - Standard Transparent Lid	100	100	90	60



Part Number	Description	H	W	D	QTY
FEP-0022	ABS Enclosure - Standard Grey Lid	190	140	90	20
FEP-0024	ABS Enclosure - Deep Grey Lid	190	140	135	16
FEP-0023	ABS Enclosure - Standard Transparent Lid	190	140	190	20
FEP-0025	ABS Enclosure - Deep Transparent Lid	190	140	135	16



Part Number	Description	H	W	D	QTY
FEP-0026	ABS Enclosure - Standard Grey Lid	240	190	100	10
FEP-0028	ABS Enclosure - Deep Grey Lid	240	190	155	4
FEP-0027	ABS Enclosure - Standard Transparent Lid	240	190	100	10

Enclosures

Hinges

Locks

Handles

Accessories

Rotary Operating
Handles

Insulators

Transformer
Equipment

Index